



PROSTAR™ JR Portable Fume Extractor



With 3 m (10')
capture arm
2000 m³/h (1200 CFM)

ProStar™
By Linde

- Features**
- Flexible 3 m (10') externally articulated capture arm
 - 1.5 HP TEFC motor producing 2000 m³/h (1200 CFM) at the hood.
 - 66 cm (26") easy-to-service nanofiber filter (MERV 15)
 - Rotary starter with 4.6 m (15') power cord & casters

- Benefits**
- Compact, portable, 120 volt, single phase
 - Capture-at-source for cleaner air
 - Complies with OSHA guidelines for controlling weld fumes

Keeping your worker's breathing zone safe requires a capture-at-source extractor they will actually use. Designed to be moved and positioned effortlessly, the PROSTAR JR excels at removing weld fumes, dusts and other airborne contaminants as small as 0.5 micron with our MERV 15 rated nanofiber filter.

The capture arm's external articulation is key to easy positioning, as smoke and dust passes through the machine without contacting the swivel and pivot points of the arm. The high suction and capture velocity developed by the PROSTAR JR allows operators to capture and filter dust and fumes further away from the hood than competitive models.

Primary Filter Comes with MERV 15 Nanofiber Filter

MERV 15 efficient cartridge filter captures particles at the submicron level, and surface-loading technology allows dust to be easily dislodged during cleaning with compressed air.



DIVP-S-JR-26NF

Efficiency:	MERV 15
Filter media:	Nanofiber
Media area:	29.7 m ² (320 ft ²)
Coating:	Fire retardant
End cap:	Open/closed
Cleaning method:	Compressed air
Max. Temperature:	82° C/ 180° F
Flange:	None



Dimensions

Part Number	Arm Length m (ft.)	Arm Diameter cm (in.)	Net Weight kg (lbs.)	Product Dimensions cm (in.)		
				Width [A]	Height [C]	Length [B]
PROSTAR JR with externally articulated capture arm						
PRSFREDJR-015N1	3 (10)	15 (6)	130 (287)	82.5 (32.5)	292 (115)	84 (33)

Technical Specifications

Part Number	Motor (H.P.)	Power		Airflow m³/h (CFM)	Cord Length m (ft.)	Arm Length m (ft.)
		Phase (Hz)	@120V (amps)			
PROSTAR JR with externally articulated capture arm						
PRSFREDJR-015N1	1.5	1Ph/60Hz	13.2	2000 (1200)	4.6 (15)	3 (10)

Contact Linde Today: For more information contact your closest branch at **1-800-225-8247** or visit our store locator at www.lindecana.ca/stores.

Linde Canada Inc.
1 City Centre Drive, Suite 1200, Mississauga, Ontario, L5B 1M2
www.lindecana.ca

Linde is a company name used by Linde plc and its affiliates. The Linde logo, the Linde word and PROSTAR are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind. Copyright © 2022. Linde plc. 02/2022 P-40-4953