



Linde Services: Equipment Reference Sheet

TMVU Specifications

Equipment Type: MVE TMVU

Vaporization Method: Ambient

Maximum Flow With Steam Assist: N/A

Maximum Flow Without Steam: 9 m³ /min

Maximum Temperature With Steam: N/A

Maximum Pressure: 250 PSI (1724 kPa)

LN₂ Capacity: 7,000 m³

Length: 12.5 m

Width: 2.6 m

Height: 3.8 m

Gross Vehicle Rated Weight: 24500 kg

* 100 – 125 PSI (689 – 862 kPa) Steam supply from Customer (1" / 25.4 mm steam connections on TMVU)

Standard TMVU Equipment

Customer Connections: ½" (12.7 mm), ¾" (19.1 mm), 1" (25.4 mm),
(Female NPT) 1½" (38.1 mm), 2" (50.8 mm)

Safeties: 3 x 300 PSI (2068 kPa)

Hose: 100' (30.48 m) GN₂ / 10' (3.05 m) LN₂

Linde Services Canada

1 City Centre Drive, Suite 1200, Mississauga, Ontario, L5B 1M2

Phone 1-800-225-8247, LSCI@linde.com | www.lindecana.ca

Linde is a company name used by Linde plc and its affiliates. The Linde logo, the Linde word and IN2ERT are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind. Copyright © 2021. Linde plc. 05/2021 P-40-4818

Making our world more productive