



Linde Services: Equipment Reference Sheet

Linde Pumper Specifications

Type: 360F Flameless Linde
Pumper

Maximum Flow: 169 m³/min

Maximum Temp with hose: 80 °C

Maximum Temp with Pipe: 80 °C

Maximum Pressure: 4000 PSI (27579 kPa)

LN₂ Capacity: 7,000 m³

Length: 15.5 m

Width: 2.6 m

Height: 4 m

Gross Vehicle Rated Weight: 35,450 kg

Standard Linde Pumper Equipment

Customer Connections: ½" (12.7 mm), ¾" (19.1 mm), 1" (25.4 mm),
(Female NPT) 1½" (38.1 mm), 2" (50.8 mm)

Safeties: 250 psi (1,724 kPa), 400 psi (2,758 kPa),
600 psi (4,137 kPa), 1,200 psi (8,274 kPa),
3,000 psi (20,684 kPa)

Hose: 100' (30.48 m) GN₂ / 10' (3.05 m) LN₂

Linde Services Canada

1 City Centre Drive, Suite 1200, Mississauga, Ontario, L5B 1M2

Phone 1-800-225-8247, LSCI@linde.com | www.lindecana.ca

Linde is a company name used by Linde plc and its affiliates. The Linde logo, the Linde word and IN2ERT are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind. Copyright © 2021. Linde plc. 05/2021 P-40-4818

Making our world more productive