

SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

## SECTION 1: Identification of the substance or mixture and of the company

#### 1.1 Product Identifier

Product name	:	Liquid Helium
Chemical name	:	Helium
Chemical formula	:	Не
CAS no.	:	7440-59-7

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses:Industrial and professional. Balance gas for mixtures. Balloon gas.<br/>Calibration gas. Carrier gas. Combustion, melting and cutting processes.<br/>Inerting gas. Laboratory use. Laser gas. Pressure head gas, operational<br/>assist gas in pressure systems. Process gas. Professional diving. Purge gas.<br/>Test gas.<br/>It is the responsibility of the end user to ensure that the product as supplied<br/>is suitable for its intended use.

#### 1.3 Details of the supplier of the safety data sheet

Supplier name	:	Linde HKO Limited
Address	:	12 Chun Yat Street, Tseung Kwan O Industrial Estate, Tseung Kwan O,
		Kowloon, Hong Kong
Phone no.	:	(852) 2372-2288
Fax no.	:	(852) 2372-2508

#### 1.3 Emergency telephone number

Emergency no.	: (852) 2661 0920 (24 hours)
---------------	------------------------------

SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

Linde

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

:

Gases under pressure (Refrigerated liquefied gas)

: H281: Contains refrigerated gas; may cause cryogenic burns or injury.

#### 2.2 Label Elements

Pictograms

		· · · · · · · · · · · · · · · · · · ·
Signal word	:	Warning
Hazard statements	:	H281: Contains refrigerated gas; may cause cryogenic burns or injury.
Precautionary statements		
General	:	None
Prevention	:	P282: Wear cold insulating gloves and either face shield or eye protection.
Response	:	P336+P315: Thaw frosted parts with lukewarm water. Do not rub affected
		area. Get immediate medical advice/attention.
Storage	:	P403: Store in a well-ventilated place.
Disposal	:	None

#### 2.3 Other hazards

None



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

## SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Chemical name	:	Helium
Chemical formula	:	Не
CAS no.	:	7440-59-7
EC no.	:	231-168-5
INDEX no.	:	
REACH registration number	:	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH),
		exempted from registration.

Ingredient(s)	CAS No.	EC no.	Purity
Helium	7440-59-7	231-168-5	≥99.999%

#### 3.2 Mixtures

Not Applicable

## SECTION 4: First Aid Measures

#### 4.1 Description of first aid measures

Inhalation	<ul> <li>In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.</li> </ul>
Eye contact	<ul> <li>Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.</li> </ul>
Skin Contact	: Contact with evaporating liquid may cause frostbite or freezing of skin. If clothing is saturated with the liquid and adhering to the skin then the area should be thawed with lukewarm water prior to removing the clothing. Not relevant, due to the form of the product.
Ingestion	: Ingestion is not considered a potential route of exposure.





SDS No.: HKO-005L

Revision date: 29/11/2022 Version no.: 03

#### 4.2 Most important symptoms and effects, both acute and delayed

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

#### 4.3 Immediate medical attention and special treatment needed

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

<b>SECTION 5: Fi</b>	refighting	Mascurac
	nengnun	

#### 5.1 Extinguishing media

Suitable extinguishing media : Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.

# 5.2 Special hazards arising from the substance or mixture None

#### 5.3 Advice for firefighters

Special fire fighting procedures	:	In case of fire, stop leak if safe to do so. Continue water spray from
		protected position until container stays cool. Use extinguishants to contain
		the fire. Isolate the source of the fire or let it burn out.
Special protective equipment for	:	Firefighters must use standard protective equipment including flame
firefighters		retardant coat, helmet with face shield, gloves, rubber boots, and Self-
		Contained Breathing Apparatus (SCBA).

## SECTION 6: Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

#### 6.2 Environmental Precautions

Prevent further leakage or spillage if safe to do so.



SDS No.: HKO-005L

Revision date: 29/11/2022 Version no.: 03

#### 6.3 Methods and material for containment and cleaning up

Provide adequate ventilation. Liquid spillages can cause embrittlement of structural materials.

#### 6.4 Reference to other sections

See also sections 8 and 13.

#### SECTION 7: Handling and Storage

#### 7.1 Precautions for safe handling

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Keep equipment free from oil and grease. Open valve slowly to avoid pressure shock. Use only oxygen approved lubricants and sealants. Use only with equipment cleaned for oxygen service and rated for the pressure. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

#### 7.2 Conditions for safe storage, including any incompatibilities

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

#### 7.3 Specific end uses

None

## SECTION 8: Exposure Controls/Personal Protection

#### 8.1 Control parameters

Occupational Exposure Limits	:	No exposure limits have been established for this product.
Biological limits	:	No biological limits have been established for this product.

#### 8.2 Exposure controls

Appropriate engineering controls : Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment.

Eye protection	:	Wear safety glasses.
Hand Protection	:	Wear leather or insulated gloves.
Body protection	:	Wear coveralls and safety boots.
Respiratory Protection	:	Where an inhalation risk exists, wear Self Contained Breathing Apparatus
		(SCBA) or an Air-line respirator.



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

## SECTION 9: Physical and Chemical Properties

#### 9.1 Information on basic physical and chemical properties

Appearance

Physical state	:	Gas
Form	:	Compressed gas
Colour	:	Colorless
Odour	:	Odourless
Odour Threshold	:	No data available.
рН	:	No data available.
Melting Point	:	-272.15 °C
Boiling Point	:	-269 °C
Sublimation Point	:	No data available.
Critical Temp. (°C)	:	-268.0 °C
Flash Point	:	No data available.
Evaporation Rate	:	No data available.
Flammability (solid, gas)	:	This product is not flammable
Flammability limit - upper (%)	:	No data available.
Flammability limit – lower (%)	:	No data available.
Vapour pressure	:	No data available.
Vapour density (air=1)	:	0.138 (0 °C)
Relative density	:	No data available.
Solubility (in Water)	:	2.5 mg/l (21 °C)
Partition coefficient (n-	:	No data available.
octanol/water)		
Autoignition Temperature	:	No data available.
Decomposition Temperature	:	No data available.
Viscosity		
Kinematic viscosity	:	No data available.
Dynamic viscosity	:	0.025 mPa.s
Explosive properties	:	No data available.
Oxidising Properties	:	No data available.

#### 9.2 Other information

None



SDS No.: HKO-005L

Revision date: 29/11/2022 Ve

Version no.: 03

## SECTION 10: Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazard other than the effects described in sub-section below.

#### 10.2 Chemical Stability

Stable under normal conditions.

#### 10.3 Possibility of Hazardous Reactions

None.

#### 10.4 Conditions to Avoid

None

#### 10.5 Incompatible Materials

Cryogenic liquids can cause embrittlement of some metals and alter the physical properties of other materials. No reaction with any common materials in dry or wet conditions.

#### 10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

### SECTION 11: Toxicological Information

#### 11.1 Information on toxicological effects

- Acute toxicity
- Oral : Inhalation : Dermal ÷ Skin Corrosion/Irritation : Serious Eye Damage/Eye Irritation : Respiratory or Skin Sensitisation : Germ Cell Mutagenicity Carcinogenicity : Reproductive toxicity : Specific Target Organ Toxicity Single Exposure **Repeated Exposure** : Aspiration Hazard
- Based on available data, the classification criteria are not met.
  - Based on available data, the classification criteria are not met.
  - Based on available data, the classification criteria are not met.
  - Based on available data, the classification criteria are not met.
  - : Based on available data, the classification criteria are not met.
  - : Based on available data, the classification criteria are not met.
  - : Based on available data, the classification criteria are not met.
  - : Based on available data, the classification criteria are not met.
  - : Based on available data, the classification criteria are not met.
  - Based on available data, the classification criteria are not met.
  - Based on available data, the classification criteria are not met.
  - : Not applicable to gases and gas mixtures.

## SECTION 12: Ecological Information

#### 12.1 Toxicity

No ecological damage caused by this product.

#### 12.2 Persistence and Degradability

Not applicable.

#### 12.3 Bioaccumulative Potential

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

#### 12.4 Mobility in Soil

Because of its high volatility, the product is unlikely to cause ground or water pollution.

#### 12.5 Other Adverse Effects

No ecological damage caused by this product.



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

## SECTION 13: Disposal Considerations

#### 13.1 Waste treatment methods

- Disposal method
- : Do not discharge into any place where its accumulation could be dangerous. Cylinders should be returned to the supplier for disposal of contents.

## SECTION 14: Transport Information

ADR/RID	
14.1 UN Number	: UN 1963
14.2 UN proper shipping name	: HELIUM, REFRIGERATED LIQUID
14.3 Transport Hazard Class(es)	
Class	: 2
Label(s)	: 2.2: Non-flammable, non-toxic gases
Classification Code	: 3A
Hazard No.	: 22
14.4 Packaging group	: None
14.5 Environmental hazards	: Not Applicable
14.6 Special precautions for user	: None
IMDG	
14.1 UN Number	: UN 1963
14.2 UN proper shipping name	: HELIUM, REFRIGERATED LIQUID
14.3 Transport Hazard Class(es)	
Class	: 2.2
Label(s)	: 2.2: Non-flammable, non-toxic gases
14.4 Packaging group	: None
14.5 Environmental hazards	: Not Applicable
14.6 Special precautions for user	: None



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

ΙΑΤΑ		
14.1 UN Number	:	UN 1963
14.2 UN proper shipping name	:	HELIUM, REFRIGERATED LIQUID
14.3 Transport Hazard Class(es)		
Class	:	2.2
Label(s)	:	2.2: Non-flammable, non-toxic gases
14.4 Packaging group	:	None
14.5 Environmental hazards	:	Not Applicable
14.6 Special precautions for user	:	None
Other information		
Passenger and cargo aircraft	:	Allowed
Cargo aircraft only	:	Allowed

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not Applicable

#### 14.8 Additional information

Transport precautions: Avoid transport on vehicles where the load space is not separated from the<br/>driver's compartment. Ensure vehicle driver is aware of the potential<br/>hazards of the load and knows what to do in the event of an accident or an<br/>emergency. Before transporting product containers ensure that they are<br/>firmly secured. Ensure that the container valve is closed and not leaking.<br/>Container valve guards or caps should be in place. Ensure adequate air<br/>ventilation.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Local legislation : Dangerous Goods Ordinance (Chapter 295)



SDS No.: HKO-005L

Revision date: 29/11/2022

Version no.: 03

SECTION 16: Other Information	
Other information :	Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.
	29/11/2022 The above information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

End of document