

Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 1/9

SECTION 1: Identification of the hazardous chemical and of the supplier

1.1. Product identifier

Product form Substance

Trade name i) Argon, Refrigerated Liquid

ii) PCC Argon, Refrigerated Liquid

CAS-No. 7440-37-1 **Formula** Ar

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Supplier's details

Linde Gas Products Malaysia Sdn Bhd (453560-K) P.O. Box 10633, GPO Kuala Lumpur, 50670 WPKL.

No. 1, Jalan Graphite 3, Kawasan Perindustrian Bandar Mahkota Banting,

42700 Banting, Kuala Langat, Selangor Darul Ehsan.

T oll Free: 1800 883 888 / +603 5651 7000

csc.lg.my@linde.com

1.4. Emergency telephone number

Emergency phone number (24h): 1800 883 888 Poison center : Unit HAZMAT Malaysia, tel: 999

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to Industry Code of Practice on chemicals classification and hazard communication (2014)

Press. Gas (Ref. Liq.) H28

2.2. Label elements

Labelling according to Industry Code of Practice on chemicals classification and hazard communication (2014)

Hazard pictograms (GHS MY)

 \Diamond

GHS04

Signal word (GHS MY) : Warning

Hazard statements (GHS MY) : H281 - Contains refrigerated gas; may cause cryogenic burns or injury

Precautionary statements (GHS MY)

- **Prevention** : P282 - Wear cold insulating gloves/face shield/eye protection

- **Response** : P315 - Get immediate medical advice/attention.

P336 - Thaw frosted parts with lukewarm water. Do no rub affected area

- **Storage** : P403 - Store in a well-ventilated place

2.3. Other hazards not contributing to the classification

Other hazards which do not result in Asphyxiant in high concentrations.

classification

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Name	Product identifier	%
Argon, Refrigerated Liquid (Main constituent)	(CAS-No.) 7440-37-1	100



Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 2/9

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove victim to uncontaminated area

wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform

cardiopulmonary resuscitation if breathing stopped.

First-aid measures after skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical

assistance. Wash skin with plenty of water.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Rinse eyes with water as a

precaution.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure. Call a poison center or a doctor if you feel

unwell

4.2. Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness.

Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment : None.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray or fog. Water spray. Dry powder. Foam.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Reactivity : No reactivity hazard other than the effects described in sub-sections below. **Reactivity in case of fire** : No reactivity hazard other than the effects described in sub-sections below.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

Special protective equipment for fire

fighters

: In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit

compressed air breathing apparatus with full face mask. Standard EN 137 - Sen-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for

firefighters. Standard - EN 659: Protective gloves for firefighters.

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may

cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire. Move

containers away from the fire area if this can be done without risk.

EAC code : 2T

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use protective clothing. Ensure adequate air ventilation. Prevent from

entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when

asphyxiating gases may be released.



Argon, Refrigerated Liquid

Issue date: 16/01/2013 Version: 2.1 SDS reference: MY000543 Revision date: 26/05/2023 3/9

6.1.1. For non-emergency personnel

> **Emergency procedures** : Ventilate spillage area.

6.1.2. For emergency responders

> Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to

> > section 8: "Exposure controls/personal protection".

6.2. **Environmental precautions**

Avoid release to the environment. Try to stop release. Liquid spillages can cause embrittlement of structural materials.

6.3. Methods and material for containment and cleaning up

> Methods and material for containment and cleaning up

: Ventilate area.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.

Safe use of the product

Do not breathe gas. Avoid release of product into work area. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis.

Conditions for safe storage, including any incompatibilities 7.2.

Storage conditions

: Store in a well-ventilated place. Keep cool.

Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve quards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away

from sources of heat and ignition. Keep away from combustible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

Exposure limit values for the other components

No additional information available

8.2. Monitoring



Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 4/9

8.3. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.4. Personal protective equipment

Wear safety shoes while handling containers.

Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Hand protection:

Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher. Wear cold insulating gloves when transfilling or breaking transfer connections. Standard EN 511 - Cold insulating gloves.

Eye protection

Safety glasses. Wear goggles and a face shield when transfilling or breaking transfer connections. Standard EN 166 - Personal eye-protection - specifications

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.









Thermal hazard protection : None in addition to the above sections.

Environmental exposure controls: None necessary. Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Gas

Appearance : No data available
Colour : Colourless.
Odour : Odourless

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : Not applicable for gases and gas mixtures.

Melting point, Freezing point : Melting point: -189 °C Freezing point: -189 °C

Boiling point : -186 °C

Flash point : Not applicable for gases and gas mixtures.

Critical temperature : -122 °C

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Flammability : Non flammable.

Vapour pressure : Vapour pressure: Not applicable.

Vapour pressure at 50°C: Not applicable.

Evaporation rate : Relative evaporation rate (ether=1): Not applicable for gases and gas mixtures.



Argon, Refrigerated Liquid

Issue date: 16/01/2013 Version: 2.1 SDS reference: MY000543 Revision date: 26/05/2023 5/9

Explosive limits : Non flammable. : No data available Lower explosion limit Upper explosion limit : No data available **Explosive properties** : Not applicable. Minimum ignition energy : No data available Solubility : Water: 67.3 mg/l

Density : Relative density: 1.4

: Relative vapour density at 20°C: Not applicable. Relative density

Relative gas density: 1.38

Viscosity Viscosity, dynamic: No reliable data available.

Viscosity, kinematic: 1.38No reliable data available.

Critical pressure : 4898 kPa

: Press. Gas (Ref. Liq.) Gas group

Partition coefficient n-octanol/water

(Log Pow)

: Not applicable for inorganic products.

Molecular mass : 40 g/mol Oxidising properties : Not applicable.

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

Chemical stability : Stable under normal conditions. Conditions to avoid : Avoid moisture in installation systems.

Hazardous decomposition products

Incompatible materials

: For additional information on compatibility refer to ISO 11114. Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the cryogenic conditions present in refrigerated liquefied gas systems.

Possibility of hazardous reactions

Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified Skin corrosion or irritation : Not classified

pH: Not applicable for gases and gas mixtures.

Serious eye damage or eye irritation : Not classified Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (STOT) -: Not classified

single exposure

Specific target organ toxicity (STOT) - : Not classified

repeated exposure

Aspiration hazard : Not classified



Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 6/9

i) Argon, Refrigerated Liquid ii) PCC Argon, Refrigerated Liquid (7440-37-1)	
Viscosity, kinematic (calculated value) (40 °C)	No reliable data available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available. **Hazardous to the aquatic environment,** : Not classified

short-term (acute)
Hazardous to the aquatic environment,

: Not classified

long-term (chronic)

i) Argon, Refrigerated Liquid ii) PCC Argon, Refrigerated Liquid (7440-37-1)	
Partition coefficient n-octanol/water (Log Kow)	Not applicable for gas mixtures.
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic products.

12.2. Persistence and degradability

i) Argon, Refrigerated Liquid ii) PCC Argon, Refrigerated Liquid (7440-37-1)	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

i) Argon, Refrigerated Liquid ii) PCC Argon, Refrigerated Liquid (7440-37-1)	
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Partition coefficient n-octanol/water (Log Kow)	See section 12.1 on ecotoxicology
Bioaccumulative potential	No data available.

12.4. Mobility in soil

i) Argon, Refrigerated Liquid ii) PCC Argon, Refrigerated Liquid (7440-37-1)	
Mobility in soil	No additional information available
Partition coefficient n-octanol/water (Log Pow)	See section 12.1 on ecotoxicology
Partition coefficient n-octanol/water (Log Kow)	See section 12.1 on ecotoxicology
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Other adverse effects

Ozone : Not classified

Effect on global warming : No known effects from this product.

Effect on the ozone layer : None.

Other adverse effects : Can cause frost damage to vegetation.

SECTION 13: Disposal information

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not

discharge into any place where its accumulation could be dangerous. May be vented to atmosphere in a well ventilated place. Return unused product in original container to supplier.

Additional information : External treatment and disposal of waste should comply with applicable local and/or national

: External fleatifiers and disposal of waste should comply with applicable local and/of flational

regulations.

{ Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.



Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 7/9

SECTION 14: Transportation information

14.1. UN number

 UN-No. (UN RTDG)
 : 1951

 UN-No. (IMDG)
 : 1951

 UN-No. (IATA)
 : 1951

14.2. Proper Shipping Name

 Proper Shipping Name (UN RTDG)
 : ARGON, REFRIGERATED LIQUID

 Proper Shipping Name (IMDG)
 : ARGON, REFRIGERATED LIQUID

 Proper Shipping Name (IATA)
 : Argon, refrigerated liquid

14.3. Transport hazard class(es)

UN RTDG

Transport hazard class(es) (UN RTDG) : 2.2 Danger labels (UN RTDG) : 2.2



IMDG

Transport hazard class(es) (IMDG) : 2.2 Danger labels (IMDG) : 2.2



IATA

Transport hazard class(es) (IATA) : 2.2 Danger labels (IATA) : 2.2



14.4. Packing group

Packing group (UN RTDG): Not applicablePacking group (IMDG): Not applicablePacking group (IATA): Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available



Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 8/9

14.6. Special precautions for user

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment,

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure valve is closed and not leaking, - Ensure valve outlet cap nut or pluq (where provided) is correctly fitted, - Ensure valve protection device

(where provided) is correctly fitted.

- UN RTDG

Limited quantities (UN RTDG) : 120 ml

Excepted quantities (UN RTDG) : E1

Packing instruction (UN RTDG) : P203

Portable tank and bulk container : T75

special instructions (UN RTDG)

Portable tank and bulk container

special provisions (UN RTDG)

: TP5

- IMDG

Limited quantities (IMDG): 120 mlExcepted quantities (IMDG): E1Packing instructions (IMDG): P203Tank instructions (IMDG): T75Tank special provisions (IMDG): TP5

EmS-No. (Fire) : F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES

EmS-No. (Spillage) : S-V - SPILLAGE SCHEDULE Victor - GASES (NON-FLAMMABLE, NON-TOXIC)

Stowage category (IMDG) : D

Properties and observations (IMDG) : Liquefied, inert gas. Heavier than air (1.4).

MFAG-No : 120

- IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity : Forbidden

(IATA)

PCA packing instructions (IATA) : 202
PCA max net quantity (IATA) : 50kg
CAO packing instructions (IATA) : 202
CAO max net quantity (IATA) : 500kg
ERG code (IATA) : 2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

14.8. Hazchem or Emergency Action Code

EAC code : 2T.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Occupational Safety and Health Act 1994 and relevant regulations:

Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.



Argon, Refrigerated Liquid

 Issue date:
 16/01/2013
 Version: 2.1
 SDS reference: MY000543

 Revision date:
 26/05/2023
 9/9

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

Environment Quality Act 1974 & regulations:

Environment Quality (Clean Air) Regulations 2014.

Environmental Quality (Scheduled Wastes) Regulations 2005.

15.2. Chemical safety assessment

SECTION 16: Other information

Version : 2.1

 Issue date
 : 16/01/2013

 Revision date
 : 26/05/2023

 Supersedes
 : 05/03/2022

Abbreviations and acronyms : ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No

1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures
PBT - Persistent, Bioaccumulative and Toxic
vPvB - Very Persistent and Very Bioaccumulative
STOT- SE - Specific Target Organ Toxicity - Single Exc

STOT- SE : Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard UN - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA - International Air Transport Association
IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training.

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.