

Sub Contents

HOSPITALITY GASES

As the leading supplier in southern Africa of gases to the hospitality sector, Afrox provides a dedicated gases solution, which includes Handigas for cooking and heating, Suremix for beer and draught dispensing, and the carbonation of soft drink beverages. Partigas (balloon gas) is used for latex and foil balloon inflation and decorative balloon fantasies. Our Sureserve offer provides a comprehensive 'one stop' service unrivalled in the industry and deliveries by highly experienced teams. Our offer is led by sales and service coordinators on one consolidated account. More than a pure dispense gas supplier, Sureserve offers an extensive range of cylinders, equipment technology and added value services, to provide total solutions for the diverse outlets in its market place.

Handigas

A clean burning liquid petroleum gas that provides all energy users with a safe, efficient and economical alternative for a diverse range of cooking and heating applications.

Suremix

A range of carbon dioxide/nitrogen based gases, for the carbonation and dispensing of draught beers, wines and soft drinks. Special mixtures for different lagers, pilsners, ales, stouts and draught beers ensure a perfect pour every time.

Partigas

Afrox balloon gas (helium) that takes special events to new heights. It's the quick, clutter-free promotional tool that is at the heart of a floating balloon fantasy and turns any bare, bleak space into a special occasion.





Section 6

Handigas represents a significant portion of the hospitality service offer to the hospitality sector (hotels, resorts, conferencing centres, restaurants, fast foods, lodges and B&Bs) and is mainly used for cooking and heating. In all major metropoles, Handigas, Suremix and Partigas deliveries are carried out by specialised hospitality sales and service distribution teams, with all other regions in SA being serviced directly or by approved Afrox agents or distributors. Our significant footprint in SA and in neighbouring territories ensures that customers will have access to an Afrox product no matter where they are situated.

Our dedicated sales and customer engineering service teams will also ensure that required installations meet requirements in line with Afrox safety and legislated standards.

For product details on Handigas and propane, refer to section 5 - LPG.



SUREMIX GASES

Carbon Dioxide (CO₂) and CO₂ - Nitrogen (N₂) Mixtures

Applications

- Controlled storage and dispensing of all draught beers such as lagers, ales, pilsners and stouts
- Controlled storage and dispensing of soda fountain soft
- Controlled storage and dispensing of non-carbonated wines and fruit juices
- Afrox recommends the use of particular percentage mixtures in line with the requirements and recommendations of each beverage supplier.

Features	Benefits	Hazards
Colourless and odourless gas	Acts to blanket beers and soft drinks from the atmosphere	CO_2 and N_2 are asphyxiants (do not support life)
CO ₂ is soluble in water at moderate temperatures	Acts to maintain equilibrium of the gas content in beverages	CO ₂ is toxic in high concentrations
Food grade certification	Provides better control of non- refrigerated beverages	
Approved by beer and soft drink companies	Enhances appearance, aroma and taste	
CO ₂ is heavier than air	CO ₂ can be added to beverages in controlled conditions to increase soluble levels	
CO ₂ is slightly corrosive in the presence of moisture		No hazard

Suremix 100

Gas	Purity
Carbon dioxide	>99,9%
	Food grade

Material Description	Gas Content (kg/l/)	Cylinder Size (<i>l</i>)	Pressure kPa @ 20°C	Valve Outlet Connection	Item Number
Suremix 100 large	31,3/20 400	50	6 000	No 8 Male RH	569 SE
Suremix 100 small	5,6/3 500	10	6 000	No 8 Male RH	569 IE

Cylinder colour: White valved guard, ivory body, shoulder and neck Not all cylinder sizes are available at all Afrox outlets Please check with your local Afrox branch or dial 0860 020202 MSDS available from www.afrox.com



Suremix 60

Gas	Purity
Carbon dioxide/nitrogen mix	>99,9%
	Food grade

Material Description	Gas Content (kg/l)	Cylinder Size (<i>l</i>)	Pressure kPa @ 20°C	Valve Outlet Connection	Item Number
Suremix 60 large	21,3/14 300	50	20 000	No 3 Female RH-F G5/8″	566 SE
Suremix 60 small	4,4/3 000	10	20 000	No 3 Female RH-F G5/8″	566 IE

Contains 60% CO₂ and 40% nitrogen Cylinder colour: White valved guard, ivory body, purple shoulder and neck Not all cylinder sizes are available at all Afrox outlets Please check with your local Afrox branch or dial 0860 020202 MSDS available from www.afrox.com



Suremix 30

Gas	Purity
Carbon dioxide/nitrogen mix	>99,9%
	Food grade

Material Description	Gas Content (kg/l⁄)	Cylinder Size (<i>l</i>)	Pressure kPa @ 20°C	Valve Outlet Connection	Item Number
Suremix 30 large	12,5/9 600	50	20 000	No 3 Female RH G5/8″	564 SE
Suremix 30 small	2,8/2 100	10	20 000	No 3 Female RH G5/8″	564 IE



Cylinder colour: White valved guard, ivory body, green shoulder and neck

Not all cylinder sizes are available at all Afrox outlets

Please check with your local Afrox branch or dial 0860 020202

MSDS available from www.afrox.com



Gas	Purity
Nitrogen	>99,9%
	Food grade

Material Description	Gas Content (kg/l⁄)	Cylinder Size (l/)	Pressure kPa @ 20°C	Valve Outlet Connection	Item Number
Suremix N large	10,9/9 400	50	20 000	G3/4" RH-F	567 SE
Suremix N small	2,2/1 900	10	20 000	G3/4" RH-F	567 IE

Cylinder colour: Ivory body, grey shoulder and neck Not all cylinder sizes are available at all Afrox outlets Please check with your local Afrox branch or dial 0860 020202

MSDS available from www.afrox.com



Suremix Regulators

Content	Material Description	Item Number			
1	Suremix 60/30 Regulator	W003038			
1	Suremix N Regulator	W003038			
Note: For Suremix N a nitrogen (G 3/4" RH-F) valve, inlet stem and nut (Item Number W003082) must be fitted					
To convert this regulator to CO_2 (Suremix 100), user can purchase kit (Item Number W003067)					

136

	Item Number	Gas (kg)	Gas (ℓ)	Charges Pressure (kpa)	375 ml Soda Servings	Litres of Soda	Litres of Beer	50 Litre Beer Kegs	Beer g/l	Soda g/l
Suremix 30 (S)	564 IE	2,8	2 100	20 000			450	9	6	
Suremix 60 (S)	566 IE	4,4	3 000	20 000			450	9	10	
Suremix 100 (S)	569 IE	6,4	3 500	6 000	1 324	496	450	9	14	13
Suremix N (S)	567 IE	2,2	1 900	20 000	980	367				6
Suremix 30 (L)	564 SE	12,5	9 600	20 000			2 000	40	6	
Suremix 60 (L)	566 SE	21,3	14 300	20 000			2 000	40	11	
Suremix 100 (L)	569 SE	31,3	20 400	6 000	6 622	2 480	2 000	40	16	13
Suremix N (L)	567 SE	10,9	9 400	20 000	4 851	1 817				6

Average keg pressure @ 2,5 Bar

Beer = 8/9 50 \(\ell \) kegs per Suremix 100 (S) | Soda = 4/5 20 \(\ell \) syrup bags per Suremix 100 (S) (20 X 4 X 6,2)

PARTIGAS

Helium (He)

Gas	Purity
Helium	>99,9%
Impurities - air/methane	<0,9%

Features	Benefits	Hazards
Very low density, second lightest atom, approximately five times lighter than air	Ideally suited for inflating latex and foil balloons	Can cause asphyxiation at high concentrations
Colourless and odourless gas	Does not react with the latex material	
Non-reactive		

Material Description	Gas Content (kg/ℓ)	Cylinder Size (<i>l</i>)	Pressure kPa @ 20°C	Valve Outlet Connection	Item Number
Partigas large	1,51/9 075	50	20 000	G5/8" RH-F No3	528 SE
Partigas medium	0,6/3 600	20	20 000	G5/8" RH-F No3	528 JE
Partigas small	0,13/780	10	20 000	G5/8" RH-F No3	528 UE



Due to its non-flammability and very low density, it is ideally suited for filling floating latex and foil balloons

Sub Contents

- Small parties
- Weddings and any special events
- Corporate promotions and exhibitions
- Blimp and large volume requirements.

Note: As helium is the second smallest molecule, the gas will penetrate the smallest opening in the balloon


Cylinder colour: Lime green valved guards, brown body, shoulder and neck

All cylinder sizes may not be available from all Afrox outlets, and can be ordered in line with customer requirements.

Please check with your local Afrox branch or dial 0860 020202

Other sized cylinders may also be available on request

MSDS available from www.afrox.com



Balloon Inflator

Content	Material Description	Item Number		
1	Conwin Classic Inflator	W101531		
(Also available for short term use available on payment of a refundable deposit)				

Conwin's Classic Inflators are designed for convenience and reliability. The classic line is available with either a Soft-Touch Push Valve or a Flex-Tilt Valve outlet to suit your personal preference. The Soft-Touch Push Valve Extension Tip or Flex-Tilt Valve enables the Classic inflator to inflate latex and foil balloons. Optional pressure gauge measures how much helium is in the cylinder and enables users to calculate the number of balloons that can be inflated.

Manually inflates latex balloons

Place the balloon over the latex outlet and press downward on the Soft-Touch Push Valve until balloon has reached desired size. Use Conwin's Balloon Tying Discs to quickly and easily tie and attach ribbon.

Manually inflates foil balloons

Place the neck of the foil onto extension tip of the Soft-Touch Push Valve and begin inflating. For best results, inflate foil balloons as slowly as possible and remove balloon from the outlet while there are still wrinkles along the seam line. Autoshut off inflators are available for specific use on foil balloons and these can be imported from our global Linde vendor, with a wide range of other equipment and accessories also available. Please contact the Afrox Product Manager for more information.



The Classic Inflator includes:

- The Balloon Outlet (Soft-Touch Push Valve)
- 1 Pressure Gauge (models available with or without gauge)
- 1 Ribbon Cutter
- 1 Disc Tyer Post